

## **Description:**

It works with professional amplifier and audio processor, forming a set of high-end entertainment professional sound system with perfect sound effects and outstanding vocal performance. It is suitable for music bars, karaoke rooms, high-end conference rooms and auditoriums, etc. It can also work with the subwoofer to compose a high-performance satellite box.

## Feature:

- $^{\star}$  Use a neodymium magnet mid-woofer and a compressed neodymium magnet tweeter.
- \* 15mm birch housing, light weight, wear-resistant spray paint treatment, and dust-proof net cotton inside.

  \* The frequency divider in precise design optimizes power response and the medium frequency performance of the vocal.
- \* Multiple screw hoisting holes, a pole socket with a diameter of 35mm, various installation methods.

## Specification:

Model	TS-810	TS-812	TS-815
Impedance	8Ω	8Ω	8Ω
Frequency response	45Hz~20KHz	45Hz~20KHz	40Hz~20KHz
Rated power	300W	400W	500W
Peak power	1200W	1600W	2000W
Sensitivity	98dB/W/M	99dB/W/M	100dB/W/M
Max SPL(rated/peak)	123dB/129dB	125dB/131dB	127dB/133dB
Coverage angle	(H)90° (V)70°	(H)90° (V)70°	(H)90° (V)70°
Tweeter	1.5" compressed tweeter ×1	1.5" compressed tweeter ×1	1.7 " compressed tweeter ×1
Woofer	10" woofer ×1	12" woofer ×1	15" woofer ×1
Size (H×W×D)	524×300×340mm	600×350×382mm	680×430×430mm
Weight	12.22Kg	16Kg	22Kg