



Network Active Speaker

TR-0730



Description

The supporting small space conference room is used in the central control system. And the desktop bookshelf box is exquisite and beautiful, with exquisite craftsmanship, showing high-grade temperament.

Features

- * Built-in 1 channel network hardware audio decoding module to realize the network transmission of 16-bit CD sound quality audio signal.
- * Built-in dual power amplifier, digital bass amplifier, powerful low frequency, high efficiency amplifier; analog high-pitched amplifier to ensure soft sound quality.
- * Digital products are easy to expand and not limited by geographical location. There is no need to increase the equipment room management equipment. They adopt the common network free line construction design concept which are easy to install.

Specifications

Model	TR-0730
Rated power	Bass 2*12W, treble 2*0.5W
Network Interface	Standard RJ45 input
Transmission rate	100Mbps
Audio format	MP3
Audio mode	16-bit CD sound quality
Sampling Rate	48KHz
Frequency response	70Hz ~ 20KHz (with the local test curve)
Harmonic distortion	≤1%
SNR	>68dB(A) (bass)
Maximum power consumption of the whole machine	≤60W
Protecting circuit	Overload, short circuit protection (bass)
Working temperature	-10°C~+45°C
Working environment humidity	20% to 80% relative humidity, no condensation
Working power	~110V-240V 50Hz-60Hz
Weight	3.3Kg
Dimensions	240*160*205mm (including net cover)