



Description

The T-1S01 is a public address pre-amplifier with five balanced MIC inputs, three AUX level inputs and one EMC(priority) level input. Priority mute is achieved via MIC 2 and EMC for overriding music for paging and emergency alarm. Individual gain controls are provided for MIC and AUX input, bass and treble control is provided for overall tone control.

Features

- * 5-channel MIC input and 3-channel Aux input.
- * With 1-channel EMC input.
- * Independent volume control, MASTER volume control.
- * With compulsive insert and Priority function.
- * MIC balance input interface with phantom power.
- * Individual Gain control for MIC.
- * EMC has priority over all inputs except MIC 2 $^{\prime}$
- * Bass and Treble Tone Control.
- * AC 110V or 230V and DC 24V operation.

Specifications

Model	T-1S01
Input	MIC 1, 2, 3, 4, 5: 5mV/600Ω Balanced AUX 1, 2, 3: 10KΩ/200mV, Unbalanced
Output	600Ω/1V/0dBV
Frequency Response	20Hz~20KHz (±1dB)
S/N Ratio	MIC input: 80dB
	AUX input: 85dB
Tone	Bass: ±10dB at 100Hz
	Treble: ±10dB at 10KHz
Power Supply	~110V-230V 50/60Hz
Dimensions	484 x 298 x 44mm
Weight	4.22Kg

Rear Panel

