



# Mixer Amplifier (Phone Jack MIC Input)

## T-60M



### Features

- \* 3 MIC inputs, 2 AUX inputs.
- \* 3 MIC volume control, 2 AUX volume control.
- \* With priority, MIC1 input is prior to other audio inputs.
- \* Separate treble and bass adjustment knob.
- \* One MIC2 / AUX1 selector switch, one MIC3 / AUX2 selector switch.
- \* Two types of power output: 4 ohm, 8 ohm and 70V, 100V output.
- \* Single-channel rated power 35W / 60W output.

### Specifications

<b>Model</b>	T-60M
<b>Rated Power Output</b>	60W
<b>Speaker Outputs</b>	70V, 100V & 4-8Ω
<b>Input Sensitivity &amp; Impedance</b>	MIC 1, 2, 3: 5mV/600Ω MIC2: 775mV/10KΩ AUX2: 350mV/10KΩ
<b>Output Sensitivity &amp; Impedance</b>	MIX OUT: 1V/470Ω
<b>Tone</b>	Bass: ±10dB at 100Hz Treble: ±10dB at 10KHz
<b>Frequency Response</b>	50Hz~16KHz (+1dB, -3dB)
<b>S/N Ratio</b>	MIC 1, 2, 3: 66dB, AUX 1, 2: 80dB
<b>THD</b>	Less than 0.5% at 1KHz, 1/3 rated power
<b>Crosstalk</b>	≤50dB
<b>Cooling</b>	Fan automatically start up when temp reaches 55°C
<b>Protection</b>	High temp, overload & short-circuit
<b>Power Supply</b>	~110V-230V 50/60Hz
<b>Power Consumption</b>	100W
<b>Weight</b>	3.5Kg
<b>Dimensions</b>	484 x 335 x 88mm
<b>Finish</b>	Panel: aluminum plate, black Case: SPCC Panel

### Rear Panel

